Technical Sheet

CLR Plus SK A4

Countersunk Concrete Screws Stainless Steel A4

The stainless steel countersunk head is often used in corrosive environments when the screw must remain flush with the object to be fixed, for aesthetical reasons or to avoid interferences above it.



Applications

Material

- A4 Stainless steel

Suitable on

- Cracked and uncracked concrete

Technical Data

Product dimensions

Viite	Metallic fixings dimensions							
	Tuotenumero	Muu						Mitat ja ominaisarvot[mm]
		Reiän halkaisija [d_o][mm]	Fixing thickness (tfix) for reduced embedment depth (hef,r)	Kiinnikkeen paksuus [tf_{ix}] (1)[mm]	Fixing thickness (tfix) for increased embedment depth (hef,max)	Määrä / pakkaus[pcs]	Määrä per ulkolaatikko	Dim[mm]
CLR Plus SK A4 8x100	7210700810000	8	55	45	35	50.0	200	8x100
CLR Plus SK A4 8x120	7210700812000	8	75	65	55	50.0	200	8x120
CLR Plus SK A4 10x120	7210701012000	10	65	45	35	50.0	200	10x120

Special order item. Please contact Customer Service for further information.

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00
Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta