

Technical Sheet

SIMPSON

Strong-Tie

DSPIX4

Decking Screw Pro - Impreg®X4

The DSIX4 decking screws are designed for treated wood. The screws have a 6 lobe recess to ensure good grip. The type 17 point drives the screw efficiently and prevents wood splitting.

Features

Features

- 6-lohkoinen vetokärki
- Lakkapää
- Karkea kierre
- Tyyppi 17 piste
- Impreg® X4-pinnoite

Applications

Suitable for


- Puulattialaudat



DSPIX4

Decking Screw Pro - Impreg®X4

Technical Data



Mitat ja ominaisarvot

Viite	Mitat								
	Tuotenumero	Muu		Mitat ja ominaisarvot[mm]					
		NOBB nr.	Paino[kg]	D[mm]	L[mm]	d _h [mm]	lg ₁ [mm]	lg ₂ [mm]	Bit[mm]
DSPIX44.8X60	74356	53293705	0.005	4.8	60	6.5	26	12	T-20
DSPIX44.8X70	74357	53293713	0.005	4.8	70	6.5	32	18	T-20
DSPIX45.5X80	74358	53293724	0.009	5.5	80	7	37.5	20	T-25
DSPIX46.5X95	74359	53293732	0.015	6.5	95	8	40	29	T-30

Tuotteen ominaisuudet

Viite	Screw Parameters				
	Tyypillinen vääntölujuus - f _{tor,k} [Nm]				
	Taivutuslujuus - M _{y,k} [Nm]	Tyypillinen vetoparametri - f _{ax,k,90°} [N/mm ²]	Tyypillinen läpivetoparametri - f _{head,k} [N/mm ²]	Tyypillinen vetolujuus - f _{tens,k} [kN]	Vääntösuhde
DSPIX44.8X60	5951	15.1	32.2	7.9	1.8
DSPIX44.8X70	5951	15.1	32.2	7.9	1.8
DSPIX45.5X80	11193	15.7	33.3	12.2	1.8
DSPIX46.5X95	13203	15.8	45.7	12.9	1.5

