

Technical Sheet

SIMPSON**Strong-Tie**

GSB

Drywall to Steel Screw - Drill Point

GSB is a drywall screw with drill point. Used indoors for fixing drywall boards to steel joists from 1.0 mm up to 2.0 mm. The duplex head prevents the paper on the drywall board from tearing when fastening.

Features

Features

- Ristipää.
- Bugle-pää.
- Porakärki.
- Metallinen kierteitys.
- Fosfatoitu pinnoite.

Applications

Suitable for

- Kipsilevy teräkseen



GSB

Drywall to Steel Screw - Drill Point

Technical Data

Mitat

Viite	Mitat						
	Tuotenumero	Muu	Mitat ja ominaisarvot[mm]				
		Paino[kg]	D[mm]	L[mm]	dh[mm]	lg[mm]	Bit[mm]
GSB3.5X25	74314	0.001	3.4	25	8.2	19.5	PH2
GSB3.5X40	74313	0.003	3.4	40	8.2	34.5	PH2
GSB3.9X48	74315	0.003	3.8	48	8.2	40.5	PH2
GSB4.2X75	74295	0.005	4.1	75	8.2	53	PH2

GSB-pakattu ruuvit

Viite	Mitat					
	Tuotenumero	Mitat ja ominaisarvot[mm]				
		D[mm]	L[mm]	dh[mm]	lg[mm]	Bit[mm]
GSB3.5X25 Collated	74310	3.4	25	8.2	19.5	PH2
GSB3.5X40 Collated	74311	3.4	40	8.2	34.5	PH2

* Flat tape collated for standard auto-feed screwdrivers

