

Technical Sheet

SIMPSON

Strong-Tie

GK

Drywall to Wood or Steel Screw

GK drywall screws are used indoors for fixing drywall boards to wood battens and steel joists with a maximum thickness of 1.0 mm. The duplex head prevents the paper on the plasterboard from tearing when fastening.

Features


Features

- PH-käyttö
- Kaksipuolinen pää
- Terävä kärki
- Korkea-matala kierre
- Sähkögalvanoitu pinnoite

Applications

Liitos

- Kipsilevy puuhun.
- Kipsilevy teräkseen.



GK Drywall to Wood or Steel Screw

Technical Data

Mitat

Viite	Mitat						
	Tuotenumero	Muu	Mitat ja ominaisarvot[mm]				
		Paino[kg]	D[mm]	L[mm]	dh[mm]	lg[mm]	Bit[mm]
GK3.9X30	74299	0.002	3.9	30	8	25.5	PH2
GK3.9X30 Bulk	75336	0.002	3.9	30	8	25.5	PH2
GK3.9X40	74301	0.002	3.9	40	8	35.5	PH2
GK3.9X40 Bulk	75337	0.003	3.9	40	8	35.5	PH2
GK3.9X55	74303	0.003	3.9	55	8	50.5	PH2

GK-kokoelmat

Viite	Mitat					
	Tuotenumero	Mitat ja ominaisarvot[mm]				
		D[mm]	L[mm]	dh[mm]	lg[mm]	Bit[mm]
GK3.9X30 Collated	74296	3.9	30	8	25.5	PH2
GK3.9X40 Collated	74297	3.9	40	8	35.5	PH2
GK3.9X55 Collated	74298	3.9	55	8	50.5	PH2

* Flat tape collated for standard auto-feed screwdrivers

