

Technical Sheet

SIMPSON

Strong-Tie

GT

Drywall to Wood Screw

GT drywall to wood screws are used indoors for fixing drywall boards to wood battens. The duplex head prevents the paper on the plasterboard from tearing when fastening.

Features


Features

- PH-kierre
- Kaksipuolinen pää
- Terävä kärki
- Karkea kierre
- Sähkögalvanoitu pinnoite

Applications

Suitable for


- Kipsilevy puuhun



GT Drywall to Wood Screw

Technical Data

Mitat



Viite	Mitat						
	Tuotenumero	Muu	Mitat ja ominaisarvot[mm]				
		Paino[kg]	D[mm]	L[mm]	dh[mm]	lg[mm]	Bit[mm]
GT3.9X30	75334	0.002	3.9	30	8	25.5	PH2
GT3.9X30 Bulk	74349	0.002	3.9	30	8	25.5	PH2
GT3.9X30 Bulk XL	75332	0.002	3.9	30	8	25.5	PH2
GT3.9X40	75335	0.002	3.9	40	8	25.5	PH2
GT3.9X40 Bulk	74351	0.003	3.9	40	8	25.5	PH2
GT3.9X40 Bulk XL	75333	0.003	3.9	40	8	25.5	PH2
GT3.9X55	74367	0.003	3.9	55	8	50.5	PH2
GT3.9X75	74368	0.004	3.9	75	8	50	PH2

GT-pakatut ruuvit

Viite	Mitat					
	Tuotenumero	Mitat ja ominaisarvot[mm]				
		D[mm]	L[mm]	dh[mm]	lg[mm]	Bit[mm]
GT3.9X30 Collated	74347	3.9	30	8	25.5	PH2
GT3.9X40 Collated	74348	3.9	40	8	25.5	PH2

* Flat tape collated for standard auto-feed screwdrivers

