

Technical Sheet

SIMPSON

Strong-Tie

UGTS

Exterior-Drywall to Steel or Wood Screw

UGTS screws are used for fixing exterior sheathing to wood battens and steel joists of 1.0 mm maximum thickness. The head is designed to meet the requirements of fitting exterior drywall boards.

Features

Features

- Ristipisteveto.
- Pidennetty trumpettikärki.
- Terävä kärki.
- Korkea-matala kierre.
- Protec-pinnoite.

Applications

Liitos

- Ulkopuolinen kipsilevy ja tuulilevy puuhun.
- Ulkoseinän kipsilevy ja tuulilevy teräsrakenteeseen.



Technical Sheet

SIMPSON**Strong-Tie®**

UGTS

Exterior-Drywall to Steel or Wood Screw

Technical Data

Mitat

Viite	Mitat					
	Tuotenumero	Muu	Mitat ja ominaisarvot[mm]			
		Paino[kg]	D[mm]	L[mm]	dh[mm]	Bit[mm]
UGTS3.9X30	74307	0.001	3.9	30	8.9	PH2

UGTS-pakatut ruuvit

Viite	Mitat				
	Tuotenumero	Mitat ja ominaisarvot[mm]			
		D[mm]	L[mm]	dh[mm]	Bit[mm]
UGTS3.9X30 Collated	74305	3.9	30	8.9	PH2

* Flat tape collated for standard auto-feed screwdrivers

Simpson Strong-Tie / Gbo Fastening
Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®

Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta

UGTS
**Exterior-Drywall to Steel or Wood
Screw**

www.strongtie.fi**SIMPSON****Strong-Tie®**