

Technical Sheet

SIMPSON

Strong-Tie

FBCB

Fibre Cement Screw, Drillpoint

FBCB screws are used in humid conditions both indoor and outdoor. They are particularly suited for fixing fibre cement boards to steel joists with a maximum thickness of 2.0 mm.

Features

Materiaali

- Korroosiosuoja: Impreg[®]+

Hyödyt

- PH-käyttö
- Upotettu pää ja ripat
- Porausjärki
- Impreg[®]+ pinnoite

Applications

Liitos

- Kuitusementti teräkseen




FBCB

Fibre Cement Screw, Drillpoint

Technical Data

Mitat



Viite	Mitat					
	Tuotenumero	Mitat ja ominaisarvot[mm]				
		D[mm]	L[mm]	dh[mm]	h _e [mm]	Bit[mm]
FBCB3.9X25	75456	3.9	25	6.8	15	PH2
FBCB3.9X35	75457	3.9	35	6.8	26	PH2

FBCB-kierretulpat

Viite	Mitat					
	Tuotenumero	Mitat ja ominaisarvot[mm]				
		D[mm]	L[mm]	dh[mm]	h _e [mm]	Bit[mm]
FBCB3.9X25 Collated	75721	3.9	25	6.8	15	PH2

* Flat tape collated for standard auto-feed screwdrivers
Also available Quik Drive collated

