

Technical Sheet

SIMPSON

Strong-Tie

RSND34G

Framing Nail 34° Paper tape - Clipped Head, Ring shank - HDG

The framing nail is used for wood to wood constructions. The clipped head and the tight collation means that more nails can be loaded in the tools and the ring shank increases the withdrawal capacity.

Features

Hyödyt

- Leikattu pää (D-pää)
- Suuri vetolujuus
- Kuumasinkitty
- Renkaan rengaskierre
- Paperinauha 34°

Applications

Liitos

- Puiden kehystys



Technical Sheet

SIMPSON**Strong-Tie**

RSND34G

Framing Nail 34° Paper tape - Clipped Head, Ring shank - HDG

Technical Data

Mitat

Viite	Mitat										
	Tuotenumero	Muu				Mitat ja ominaisarvot[mm]					
		DB nr.	NOBB nr.	Määrä / laatikko	Paino[kg]	d[mm]	L[mm]	d _h [mm]	A _h [mm]	h _c [mm]	t _{fix} [mm]
RSND34G2.8X65	75762	2056109	55837755	1700	0.004	2.8	65	5	19.6	1.1	48.2
RSND34G2.8X75	75763	2056110	55837766	1500	0.004	2.8	75	5	19.6	1.1	58.2
RSND34G3.1X90	75764	2056111	55837740	1000	0.006	3.1	88	5.3	22.1	1.2	69.4
RSND34G3.1X98	76149	2124527	-	1000	0.007	3.1	96	5.3	22.1	1.3	77.4

Tuotteen ominaisuudet

Viite	Nail characteristic parameters			
	Tyypillinen vääntölujuus - f _{tor,k} [Nm]			
	Taivutuslujuus - M _{y,k} [Nm][Nm]	Tyypillinen vetoparametri - f _{ax,k,90°} [N/mm²][N/mm²]	Tyypillinen läpivetoparametri - f _{head,k} [N/mm²][N/mm²]	Tyypillinen vetolujuus - f _{tens,k} [kN][kN]
RSND34G2.8X65	3.2	9.3	22.9	3.1
RSND34G2.8X75	3.2	9.3	22.9	3.1
RSND34G3.1X90	4.7	8.6	-	3.1
RSND34G3.1X98	4.7	8.6	-	3.1

Simpson Strong-Tie / Gbo
Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®

Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta

RSND34G

Framing Nail 34° Paper tape - Clipped Head, Ring shank - HDG

www.strongtie.fi

SIMPSON**Strong-Tie**