

Technical Sheet

SIMPSON

Strong-Tie

BRDHG

Grooved Countersunk Nail - Hot Dip Galvanised

Nail with a countersunk head and grooved shank for use indoors for fitting moulding or fixing hardwood and semi-hardwood boards to a wood base.

Particularly suited for use where the head should be countersunk, so that the nail is concealed.

Features

Features

- Upotettu pää.
- Uurrettu varsi.
- Kuumasinkitty pinnoite.

Applications

Liitos

- Puu-puu liitos



Technical Sheet

BRDHG Grooved Countersunk Nail - Hot Dip Galvanised

SIMPSON**Strong-Tie®**

Technical Data



Mitat

Viite	Mitat								
	Tuotenumero	Muu					Mitat ja ominaisarvot[mm]		
		DB nr.	NOBB nr.	Määrä / laatikko	Määrä/Blisteripakkaus	Paino[kg]	d[mm]	L[mm]	d _h [mm]
BRDHG1.7X30	75595	2055949	55839586	1000	-	0.001	1.7	30	2.7
BRDHG1.7X35	74207	1950535	53291980	1000	-	0.001	1.7	35	2.7
BRDHG1.7X40	74208	1950536	53291995	1000	-	0.001	1.7	40	2.7
BRDHG1.7X50	75596	2055950	55839594	500	-	0.002	1.7	50	2.7
BRDHG2.0X40	75597	2055951	55839605	500	-	0.002	2	40	3.2
BRDHG2.0X50	74209	1950537	53292006	500	-	0.002	2	50	3.2
BRDHG2.0X50 Blister	78244	-	-	-	60.0	0.002	2	50	3.2
BRDHG2.3X60	74210	1950538	53292014	500	-	0.003	2.3	60	3.7
BRDHG2.3X60 Blister	78243	-	-	-	40.0	0.003	2.3	60	3.7
BRDHG2.8X75	74211	1950539	53292025	250	-	0.004	2.8	75	4.5
BRDHG2.8X75 Blister	78256	-	-	-	25.0	0.005	2.8	75	4.5

Simpson Strong-Tie / Gbo Fastening
Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00
Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta

BRDHG
Grooved Countersunk Nail - Hot Dip
Galvanised

www.strongtie.fi**SIMPSON****Strong-Tie®**