Technical Sheet

DSPROA4


Hardwood Decking Screw - Stainless Steel A4

Made for hardwood decking such as Cumaro, Bankirai and others. Can be used in Marine environments. Needs pre-drilling with 4 mm drill and pre-countersinking close to the edge.









Features

Materiaali

- Ruostumaton teräs A4

Ominaisuudet:

- 6-lohkoinen vetokärki
- Kaksoiskierre
- Taltta-kärki

Applications


Sovellus

- Kovapuusta valmistetut terassilaudat puuhun

Technical Sheet

DSPROA4
Hardwood Decking Screw - Stainless Steel A4

Technical Data



Mitat

Viite	Mitat							
	Muu	Mitat ja ominaisarvot[mm]						Asennus
	Paino[kg]	D[mm]	L[mm]	d_h[mm]	lg_1[mm]	lg_2[mm]	Bit[mm]	Yhden kiinnikepakkauksen riittoisuus [m²]
DSPROA45.5X50	0.005	5.5	50	7	22.5	10.5	T-25	4.4
DSPROA45.5X60	0.005	5.5	60	7	27.5	10.5	T-25	4.4
DSPROA45.5X70	0.005	5.5	70	7	32.5	10.5	T-25	4.4
DSPROA45.5X80	0.006	5.5	80	7	37.5	10.5	T-25	4.4

Tuotteen ominaisuudet

Viite	Screw Parameters				
	Tyypillinen vääntölujuus - $f_{tor,k}$ [Nm]				
	Taivutuslujuus - $My,_k$[Nm]	Tyypillinen vetoparametri - $f_{ax,k,90°}$[N/mm²]	Tyypillinen läpivetoparametri - $f_{head,k}$[N/mm²]	Tyypillinen vetolujuus - $f_{tens,k}$[kN]	Vääntösuhde
DSPROA45.5X50	7585	12.8	31.8	7.8	3.8
DSPROA45.5X60	7585	12.8	31.8	7.8	3.8
DSPROA45.5X70	7585	12.8	31.8	7.8	3.8
DSPROA45.5X80	7585	12.8	31.8	7.8	3.8

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00
Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta