Technical Sheet


CLR Plus H
Hex-Head Concrete Screws

The hexagonal head version is the standard version used for the most applications, specially with greatest diameters and higest loads to fix metallic and timber carpentry.









Applications

Material

- Electro-galvanized steel

Suitable on

- Cracked and uncracked concrete

Technical Sheet

CLR Plus H
Hex-Head Concrete Screws

SIMPSON Strong-Tie

Technical Data

Technical Sheet

CLR Plus H
Hex-Head Concrete Screws

SIMPSON Strong-Tie

Product dimensions

Viite	Metallic fixings dimensions							
	Tuotenumero	Muu						Mitat ja ominaisarvot[mm]
		Reiän halkaisija [d_o][mm]	Fixing thickness (tfix) for reduced embedment depth (hef,r)	Kiinnikkeen paksuus [tf_{ix}] (1)[mm]	Fixing thickness (tfix) for increased embedment depth (hef,max)	Määrä / pakkaus[pcs]	Määrä per ulkolaatikko	Dim[mm]
CLR Plus H 6x40	72105B0604000	6	5	-	-	100.0	1000	6x40
CLR Plus H 6x50	72105B0605000	6	15	10	-	100.0	400	6x50
CLR Plus H 6x60	72105B0606000	6	25	20	5	100.0	1000	6x60
CLR Plus H 6x80	72105B0608000	6	45	40	25	100.0	1000	6x80
CLR Plus H 6x100	72105B0610000	6	65	60	45	100.0	1000	6x100
CLR Plus H 8x60	72105B0806000	8	15	5	-	50.0	500	8x60
CLR Plus H 8x80	72105B0808000	8	35	25	15	50.0	500	8x80
CLR Plus H 8x100	72105B0810000	8	55	45	35	50.0	250	8x100
CLR Plus H 8x120	72105B0812000	8	75	65	55	50.0	250	8x120
CLR Plus H 8x140	72105B0814000	8	95	85	75	50.0	250	8x140
CLR Plus H 10x60	72105B1006000	10	5	-	-	50.0	200	10x60
CLR Plus H 10x80	72105B1008000	10	25	5	-	50.0	250	10x80
CLR Plus H 10x100	72105B1010000	10	45	25	15	40.0	200	10x100
CLR Plus H 10x120	72105B1012000	10	65	45	35	50.0	200	10x120
CLR Plus H 10x140	72105B1014000	10	85	65	55	30.0	150	10x140
CLR Plus H 10x150	72105B1015000	10	95	75	65	50.0	200	10x150

"*" = On stock
"-" = Made on demand

Technical Sheet

CLR Plus H
Hex-Head Concrete Screws

Viite	Metallic fixings dimensions							
	Tuotenumero	Muu						Mitat ja ominaisarvot[mm]
		Reiän halkaisija [d_o][mm]	Fixing thickness (tfix) for reduced embedment depth (hef,r)	Kiinnikkeen paksuus [tf_{ix}] (1)[mm]	Fixing thickness (tfix) for increased embedment depth (hef,max)	Määrä / pakkaus[pcs]	Määrä per ulkolaatikko	Dim[mm]
CLR Plus H 10x160	72105B1016000	10	105	85	75	50.0	200	10x160
CLR Plus H 10x200	72105B1020000	10	145	125	115	25.0	100	10x200
CLR Plus H 10x240	72105B1024000	10	185	165	155	25.0	100	10x240
CLR Plus H 10x280	72105B1028000	10	225	205	195	25.0	100	10x280
CLR Plus H 10x320	72105B1032000	10	265	245	235	25.0	100	10x320
CLR Plus H 10x400	72105B1040000	10	345	325	315	25.0	-	10x400
CLR Plus H 12x80	72105B1208000	12	15	-	-	25.0	250	12x80
CLR Plus H 12x110	72105B1211000	12	45	25	10	25.0	100	12x110
CLR Plus H 12x130	72105B1213000	12	65	45	30	25.0	100	12x130
CLR Plus H 12x150	72105B1215000	12	85	65	50	25.0	100	12x150
CLR Plus H 14x80	72105B1408000	14	5	-	-	25.0	100	14x80
CLR Plus H 14x110	72105B1411000	14	35	10	-	25.0	100	14x110
CLR Plus H 14x130	72105B1413000	14	55	30	15	25.0	100	14x130
CLR Plus H 14x150	72105B1415000	14	75	50	35	25.0	100	14x150

"*" = On stock
"-" = Made on demand

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita käytettäessä.

2026-11-19

www.strongtie.fi