Technical Sheet

CLR Plus H ZF


Hex-Head Concrete Screws Zinc-Flake Coated

Thezinc-flake coated hexagonal head version is the standard version used for the most applications where a coated screw is preferred, specially with greatest diameters and higest loads to fix metallic and timber carpentry.









Applications

Material

- Zinc-flake coated steel

Suitable on

- Cracked and uncracked concrete

Technical Data

Product dimensions

Viite	Metallic fixings dimensions							
	Tuotenumero	Muu						Mitat ja ominaisarvot[mm]
		Reiän halkaisija [d_o][mm]	Fixing thickness (tfix) for reduced embedment depth (hef,r)	Kiinnikkeen paksuus [tf_{ix}] (1)[mm]	Fixing thickness (tfix) for increased embedment depth (hef,max)	Määrä / pakkaus[pcs]	Määrä per ulkolaatikko	Dim[mm]
CLR Plus H ZF 6x40	72105C0604000	6	5	-	-	100.0	400	6x40
CLR Plus H ZF 6x60	72105C0606000	6	25	20	5	100.0	400	6x60
CLR Plus H ZF 6x80	72105C0608000	6	45	40	25	100.0	400	6x80
CLR Plus H ZF 6x100	72105C0610000	6	65	60	45	100.0	400	6x100
CLR Plus H ZF 8x60	72105C0806000	8	15	5	-	50.0	200	8x60
CLR Plus H ZF 8x80	72105C0808000	8	35	25	15	50.0	200	8x80
CLR Plus H ZF 8x100	72105C0810000	8	55	45	35	50.0	200	8x100
CLR Plus H ZF 8x140	72105C0814000	8	95	85	75	50.0	200	8x140
CLR Plus H ZF 10x90	72105C1009000	10	35	15	5	50.0	200	10x90
CLR Plus H ZF 10x100	72105C1010000	10	45	25	15	50.0	200	10x100

Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta