

Technical Sheet

SIMPSON

Strong-Tie

KHS
Kehysruuvi

Used indoors when fitting window and door frames with Ø14 mm pre-drilled holes. The finished assembly is adjustable. If it needs to be dismantled, the frame and wall remain intact. The fixing is fitted with a combi tool and adjusted with a T-spanner.

Features

Ominaisuudet:

- Sähkögalvanoitu
- Nopea asennus

Applications

Application:

- Ovi-/ikkunakehykset puualustoille



INDOOR

EG




Technical Sheet

KHS
Kehysruuvi

SIMPSON

Strong-Tie

Technical Data



Product dimensions

Viite	Mitat			
	Tuotenumero	Muu	Mitat ja ominaisarvot[mm]	
		NOBB nr.	L[mm]	d _n [mm]
KHS14x70	75734 - 75548	55842265 - 55841293	70	14
KHS14x90	75735 - 75549	55842273 - 55841304	90	14

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita
käytettäessä.

KHS
Kehysruuvi



www.strongtie.fi

2026-10-30

SIMPSON

Strong-Tie