

Technical Sheet

SIMPSON

Strong-Tie

LBS

Kevyt betoniruuvit

Fasten screw without pre-drilling directly into the porous stone material. Use a low rpm drilling machine but avoid tightening the screw too hard. If this happens the thread loses its grip from the bedding and a new fitting should be done. Minimum anchorage is 60 mm.

Features

Ominaisuudet:

- Protec-pinnoite
- Upotettu pää ja kärjet

Applications

Application:

- Puu kevytbetoniksi



Technical Sheet

LBS
Kevyt betoniruuvit

SIMPSON

Strong-Tie

Technical Data

Product dimensions

Viite	Metallic fixings dimensions								
	Tuotenumero	Muu			Mitat ja ominaisarvot[mm]				
		NOBB nr.	Kiinnikkeen paksuus [tfix] (°)[mm]	Paino[kg]	D[mm]	L[mm]	Pään halkaisija [s][mm]	lg	Bit
LBS8.0x65	75259	55840960	5	0.014	8	65	12	60	T-30
LBS8.0x110	75327	55838958	50	0.024	8	110	12	60	T-30
LBS8.0x130	75328	55836476	70	0.03	8	130	12	60	T-30
LBS8.0x180	75329	55836480	120	0.041	8	180	12	60	T-30
LBS8.0x210	75330	55836495	150	0.048	8	210	12	60	T-30

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®

Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita
käytettäessä.

LBS
Kevyt betoniruuvit

2026-10-30



www.strongtie.fi

SIMPSON

Strong-Tie