Technical Sheet

LBP
Kevyt betonitulppa

Used indoors for fitting kitchen units and wooden battens to porous masonry materials without pre-drilling. However when fixing to Leca, pre-drilling of a hole 1 mm less than the relevant plug diameter is required. Pre-drill the material that is to be fixed, knock in the plug with a hammer, turn no more than six turns, and the plug will expand, like a knot.





Features

Ominaisuudet:

Käytetään sisätiloissa keittiökaappien ja puurimojen kiinnittämiseen huokoisiin muurattuihin materiaaleihin ilman esiporausta. Kuitenkin, kun kiinnitetään Lecaan, vaaditaan esiporaus, jonka halkaisija on 1 mm pienempi kuin vastaavan tulpan halkaisija. Poraa kiinnitettävä materiaali, lyö tulppa sisään vasaralla, kierrä enintään kuusi kierrosta, ja tulppa laajenee solmun tavoin.

Applications

Application:

- Puu kevytbetoniksi

Technical Data

Product dimensions

Viite	Nylon fixings dimensions						
	Tuotenumero	NOBB nr.	Tuot[mm]				
			D	L	dh	Fixture thickness (tfix)	Bit
LBP6.0x50	75529	55840706	6	50	-	15	T-20
LBP6.0x70	75530	55840714	6	70	-	35	T-20
LBP8.0x60	75531	55836718	8	60	11	10	T-25
LBP8.0x80	75532	55840695	8	80	11	30	T-25
LBP8.0x100	75533	55842795	8	100	11	50	T-25
LBP8.0x120	75534	55841834	8	120	11	70	T-25
LBP8.0x140	75535	55841845	8	140	11	90	T-25
LBP10.0x100	75536	55841853	10	100	-	40	T-40
LBP10.0x120	75538	55841872	10	120	-	60	T-40
LBP10.0x140	75537	55841864	10	140	-	80	T-40
LBP10.0x460	75539	55841883	10	460	-	400	T-40

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita käytettäessä.

2026-11-19