

Technical Sheet

SIMPSON

Strong-Tie

CSFT
Kierretappi

CSFT connector screw is designed for steel to wood connections and load rated together with specific Simpson Strong-Tie connectors. The new head shape ensure a good fit in the connector and the full thread increase the load bearing capacity. The flat head makes it possible to get a flush surface after installation.

Features


Features

- CE-merkitty (EN14592)
- Kierrekierre
- Sinkkipinnoite
- 6-lohkoinen käyttö
- Erityinen päämuoto, joka on suunniteltu SST-liittimille

Applications

Suitable for

- Wood to wood



CSFT
Kierretappi

Technical Data

Product Dimensions

Viite	Mitat								
	Tuotenumero	Mitat ja ominaisarvot[mm]						Muu	
		d[mm]	L[mm]	d _h [mm]	d ₁ [mm]	lg[mm]	Bit[mm]	Määrä / laatikko	Paino[kg]
CSFT5.0X70	77308	5	70	8.5	3.5	65	T-20	100.0	0.006
CSFT6.0X85	77309	6	85	9.5	4	79	T-25	100.0	0.01
CSFT6.0X110	77310	6	110	9.5	4	103	T-25	100.0	0.013

Characteristic properties

Viite	Screw Parameters			
	Tyypillinen vääntölujuus - f _{tor,k} [Nm]			
	Taivutuslujuus - M _{y,k} [Nm][Nm]	Tyypillinen vetoparametri - f _{ax,k,90°} [N/mm²][N/mm²]	Tyypillinen vetolujuus - f _{tens,k} [kN][kN]	Torsiosuhde
CSFT5.0X70	7.7	17.8	10.7	>1,5
CSFT6.0X85	10.5	13.6	12.9	>1,5
CSFT6.0X110	10.5	13.6	12.9	>1,5

