

NEDC

NEDC Suspension Brackets

Suspension brackets are used for lowering ceilings to allow for technical installations. The product is designed in accordance with Eurocode 5 and complies with edge distance requirements.

Features

Material

- Steel:
S250GD + Z275 according to DIN EN 10346
- Corrosion protection:
275 g/m² on both sides - correspond to a zinc layer of approx. 20 µm

Benefits


To avoid damage to the vapor barriers, reinforcements have been made around the mounting holes.
For easier installation, a mounting mark has been added.

Applications

When to use

The suspension bracket is used in roof constructions where technical installations are routed at ceiling level.

The bracket is for suspending rafter planks, onto which the ceiling cladding is to be mounted.
It is used in warm attic duct spaces where ventilation pipes, water pipes, and electrical installations are routed.



Technical Sheet

SIMPSON

Strong-Tie

NEDC

NEDC Suspension Brackets

Technical Data



Product dimensions

Viite	Mitat										
	Muu				Mitat ja ominaisarvot[mm]					Reiät[mm]	
	DB nr.	NOBB nr.	Määrä per laatikko	Paino[kg]	A[mm]	B[mm]	C[mm]	D[mm]	t[mm]	Pyöreä Ø	Pitkänomainen Ø5x20
NEDC48227	-	60671909	50	0.14	227	110	48	29	1	6	2

Asennus

Fixing

- Connecting with CSA4,0x40 connector screw

