
Technical Sheet

KEM HP
Polyester Fast Cure Anchoring Adhesive

KEM HP is a polyester anchoring adhesive for medium to heavy weight applications.
The fast curing formula provides good performances when anchoring threaded rods in uncracked concrete and masonry.
Working temperature: from -40 up to +80°C short period and from -40 up to +50°C long period.





Features

Material

Polyester

Applications

Applications

- Steel constructions
- Wood to concrete fixings
- Industrial construction
- Steel and metal construction (railings, brackets, etc.)
- Anchorages for gates and machines

Suitable for

- Threaded rods in uncracked concrete
- Threaded rods in masonry
- **Suitable base materials:**
  Concrete
  Solid brick
  Honeycomb
  Cell like clay brick
  Light weight honeycomb brick
  Hollow dense aggregate block
  Hollow light aggregate block
  Aerated concrete (partially suitable)
  Solid stone1)
  Wood
  1) For application on natural stone or marble, carry out test and wait 24/48 hours for any reactions

For installation instructions and information please refer to Technical Documents.

Technical Data

KEM HP

Viite	Chemical fixings dimensions								
	Tuot								
	Nimi	DB nr. [mm]	NOBB nr.	Väri	Sisällys[ml]	Sanitary text languages	Storage months	Määrä pakkauksessa[pcs]	Pcs./pallet
951040BH00000	KEM HP 951	2604114	60867578	Blue-to-Grey	300	EN, PL, DA, NO, SV, FI	18.0	12	1152.0

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00
Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta