

Technical Sheet

SIMPSON

Strong-Tie

PHX
Post support

PHX post supports are produced in 5 or 8 mm steel.

Not for use in loadbearing constructions.

Features

Material

Steel quality:

S 235 JR acc. to DIN EN 10025

Corrosion protection:

Hot-dip galvanized; Zinc layer thickness approx. 55 µm according to DIN EN 1461

Benefits

- Direct installation in concrete, without additional connecting means.
- Stepless adjustment to column width.

Applications

Applications

- Fences
- Pergolas
- Carports
- Also for use in concrete foundations.

When to use

- Support for posts in the home and garden



Technical Sheet


PHX
Post support

SIMPSON

Strong-Tie

Technical Data

Dimensions



Viite	Mitat					
	Mitat ja ominaisarvot[mm]				Reiät	Muu
	A[mm]	B[mm]	D[mm]	t[mm]	Pyöreä Ø12	Paino[kg]
PHX376G	376	40	107	5	2	-
PHX500G	500	40	130	8	2	1.4

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita
käytettäessä.

PHX
Post support



www.strongtie.fi

2026-10-
23

SIMPSON

Strong-Tie