
Technical Sheet

KEM EP

Premium Epoxy High Strength Anchoring Adhesive with Seismic Certification

KEM EP is a high performance epoxy anchoring adhesive for heavy-duty structural fixings in seismic areas.
KEM EP provides excellent adhesive properties and low shrinkage, suitable for use with smooth/diamond cored holes.
Working temperature: from -40 up to +72°C short period and from -40 up to +50°C long period.





Features

Material

Epoxy

Applications

Applications

- Steel constructions
- Wood to concrete structural fixings
- Industrial construction
- Steel and metal construction (railings, brackets, etc.)
- Anchorages for gates and machines
- Large post-installed rebar connections

Suitable for

- For cracked and uncracked concrete with threaded rods and rebar
- Diamond drilled holes

Suitable base materials:

- Concrete
- Solid brick
- Honeycomb
- Cell like clay brick
- Light weight honeycomb brick
- Hollow dense aggregate block
- Hollow light aggregate block
- Aerated concrete (partially suitable)
- Solid stone[1)]
- Wood

1) For application on natural stone or marble, carry out test and wait 24/48 hours for any reactions

For installation instructions and information please refer to technical documents

KEM EP
Premium Epoxy High Strength Anchoring Adhesive with Seismic Certification

Technical Data

KEM EP

Viite	Chemical fixings dimensions						
	Tuot						
	Nimi	Väri	Sisällys[ml]	Sanitary text languages	Storage months	Määrä pakkauksessa[pcs]	Pcs./pallet
9340200000300	KEM EP 934	Grey	585	DA, IT, PL	24.0	12	672.0
Special order item. Please contact Customer Service for further information.							

Simpson Strong-Tie / Gbo
Fastening Systems AB
Bruksvägen 2, 593 75
Gunnebo
tel: 0490-300 00
fax : 0490-233 00
Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita käytettäessä.