Technical Sheet

ARA2C - B

Ring shank nail - Stainless A2 + Painted NCS 9000 (Black)

Stainless steel ring shank nails can be installed in outdoor environments. Used where high withdrawal strength is required. A common use is in the construction of jetties, thanks to the nail's corrosion resistance. When laying a brick facade the joins are anchored to an existing cross-wall up to 6 m.





Features

Ominaisuudet:

- Low oval head
- Ring shank
- A2 stainless steel

Applications


Sovellus

- Wood to wood

Technical Sheet


ARA2C - B
Ring shank nail - Stainless A2 + Painted NCS 9000 (Black)

Technical Data



Mitat

Viite	Mitat										
	Tuotenumero	Muu			Mitat ja ominaisarvot[mm]						
		DB nr.	NOBB nr.	Määrä / laatikko	d[mm]	L[mm]	d_h[mm]	A_h[mm]	h_t[mm]	l_p[mm]	tfix[mm]
ARA2C2.3X35B	75618	2055972	55840377	500	2.3	35	5.5	23.5	1.2	3.2	21.2



Tuotteen ominaisuudet

Viite	Nail characteristic parameters			
	Tyypillinen vääntölujuus - $f_{tor,k}$ [Nm]			
	Taivutuslujuus - $My,_k$ [Nm][Nm]	Tyypillinen vetoparametri - $f_{ax,k,90°}$ [N/mm²][N/mm²]	Tyypillinen läpivetoparametri - $f_{head,k}$ [N/mm²][N/mm²]	Tyypillinen vetolujuus - $f_{tens,k}$ [kN][kN]
ARA2C2.3X35B	1.8	6.2	29.3	3.2

Simpson Strong-Tie / Gbo
Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00
Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta