
# Technical Sheet

ARA2C - W

**Ring shank nail - Stainless Steel A2 + Painted NCS 0502-Y (White)**

Stainless steel ring shank nails can be installed in outdoor environments. Used where high withdrawal strength is required. A common use is in the construction of jetties, thanks to the nail's corrosion resistance. When laying a brick facade the joins are anchored to an existing cross-wall up to 6 m.





## Features

### Ominaisuudet:

- Low oval head
- Ring shank
- A2 stainless steel

## Applications

### Sovellus


- Puu-puu

# Technical Sheet

ARA2C - W


**Ring shank nail - Stainless Steel A2 + Painted NCS 0502-Y (White)**

# Technical Data



## Mitat

| Viite | Mitat | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | Tuotenumero | Muu | | | Mitat ja ominaisarvot[mm] | | | | | | |
| | | DB nr. | NOBB nr. | Määrä / laatikko | d[mm] | L[mm] | $d_h$[mm] | $A_h$[mm] | $h_t$[mm] | $l_p$[mm] | tfix[mm] |
| ARA2C2.3x35W | 75617 | 2055971 | 55840362 | 500 | 2.3 | 35 | 5.5 | 23.5 | 1.2 | 3.2 | 21.2 |



## Tuotteen ominaisuudet

| Viite | Nail characteristic parameters | | | |
|---|---|---|---|---|
| | Tyypillinen vääntölujuus - $f_{tor,k}$ [Nm] | | | |
| | Taivutuslujuus - $My,_k$ [Nm][Nm] | Tyypillinen vetoparametri - $f_{ax,k,90°}$ [N/mm²][N/mm²] | Tyypillinen läpivetoparametri - $f_{head,k}$ [N/mm²][N/mm²] | Tyypillinen vetolujuus - $f_{tens,k}$ [kN][kN] |
| ARA2C2.3x35W | 1.8 | 6.2 | 29.3 | 3.2 |

Simpson Strong-Tie / Gbo
Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00



Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita käytettäessä.

2026-11-19