

Technical Sheet

SIMPSON

Strong-Tie

ARA4

Ring Shank Wood to Wood Nail - Stainless Steel (A4)

This ring shank nail with its low oval head and ring shank is used to fix timber components to wood, where high pull-out strength is required. Stainless A4 can withstand all weather conditions and also deal with aggressive environments.





Technical Sheet

SIMPSON**Strong-Tie®**

ARA4

Ring Shank Wood to Wood Nail - Stainless Steel (A4)

Technical Data



Mitat ja ominaisarvot

Viite	Mitat												
	Tuotenumero	Muu					Mitat ja ominaisarvot[mm]						
		DB nr.	NOBB nr.	Määrä / laatikko	Määrä/Blisteripakkaus	Paino[kg]	d[mm]	L[mm]	d _h [mm]	A _h [mm]	h _t [mm]	l _g [mm]	l _p [mm]
ARA42.3X50	74225	1950554	53292865	500	-	0.002	2.3	50	5.5	23.8	1.4	37	2.9
ARA42.3X50 Blister	78259	-	-	-	20.0	-	2.3	50	5.5	23.8	1.4	37	2.9
ARA42.5X60	74226	1950555	53292873	250	-	0.002	2.5	60	5.7	25.5	1.3	42	3.4
ARA43.1X75	74227	1950556	53292884	250	-	0.005	3.1	75	7.5	44.2	1.8	46	4.3

Tuotteen ominaisuudet

Viite	Nail characteristic parameters			
	Tyypillinen vääntölujuus - f _{tor,k} [Nm]			
	Taivutuslujuus - M _{y,k} [Nm][Nm]	Tyypillinen vetoparametri - f _{ax,k,90°} [N/mm²][N/mm²]	Tyypillinen läpivetoparametri - f _{head,k} [N/mm²][N/mm²]	Tyypillinen vetolujuus - f _{tens,k} [kN][kN]
ARA42.3X50	1784	6.2	29.3	3.2
ARA42.3X50 Blister	1784	6.2	29.3	3.2
ARA42.5X60	2257	6	27.2	3.5
ARA43.1X75	4409	7.1	-	5.7

Simpson Strong-Tie / Gbo Fastening
Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00
Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta

ARA4
**Ring Shank Wood to Wood Nail -
Stainless Steel (A4)**

www.strongtie.fi**SIMPSON****Strong-Tie®**