

Technical Sheet

SIMPSON

Strong-Tie

PAPP

Round Clout Nail - Hot Dip Galvanised

Clout nail with a flat head and round shank that can withstand rain and is used for fixing exterior plaster board, roofing felt, asphalt board, construction membrane and draught-proofing felt to a timber base.

Features

Features

- Litteä pää
- Pyöreä kierre
- Kuumasinkitty pinnoite

Applications

Liitos

- Kattopahvi.
- Rakennuskalvo.
- Asfalttilevy.
- Ulkopuolinen kipsilevy.



Technical Sheet

SIMPSON**Strong-Tie**

PAPP

Round Clout Nail - Hot Dip Galvanised

Technical Data



Mitat

Viite	Mitat								
	Tuotenumero	Muu					Mitat ja ominaisarvot[mm]		
		DB nr.	NOBB nr.	Laatikkomäärä	Määrä/Blisteripakkaus	Paino[kg]	D[mm]	L[mm]	Pään halkaisija [d _n] [mm]
PAPP2.1X20	74212	1950540	53293285	1000	-	0.001	2.1	20	7
PAPP2.1X120 Blister	78227	-	-	-	100.0	-	2.1	20	7
PAPP2.5X25	74213	1950541	53293293	1000	-	0.001	2.5	25	8.7
PAPP2.5X25 Blister	78225	-	-	-	125.0	0.002	2.5	25	8.7
PAPP2.5X40	74214	1950543	53293304	500	-	0.002	2.5	40	8.7
PAPP2.8x20	75608	2055962	55838001	500	-	0.001	2.8	20	8.5
PAPP2.8X20 Blister	78250	-	-	-	100.0	0.002	2.8	20	8.5
PAPP2.8x25	75609 - 75610	2055963 - 2055964	55838020 - 55837997	1000 / 500	-	0.002	2.8	25	8.5
PAPP2.8x35	75611 - 75612	2055965 - 2055966	55838016 - 55837982	500 / 1000	-	0.002	2.8	35	8.5
PAPP2.5X35 Blister	78246	-	-	-	40.0	0.002	2.8	35	8.5
PAPP2.8x45	75613	2055967	55837365	500	-	0.003	2.8	45	8.5
PAPP2.8x55	75614	2055968	55837373	500	-	0.004	2.8	55	8.5
PAPP2.8x65	75615	2055969	55837384	500	-	0.004	2.8	65	8.5
PAPP2.8x75	75616	2055970	55842462	500	-	0.005	2.8	75	8.5

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®

Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson Strong-Tie:n © tuotteita käytettäessä.

PAPP
Round Clout Nail - Hot Dip Galvanised

www.strongtie.fi**SIMPSON****Strong-Tie**

2026-10-30