Technical Sheet

LTSFH
Skirting Screw Chisel Point

The floor/skirting screw is used indoors for fixing skirting or when laying hardwood flooring. The chisel point helps to prevent splitting when used on thinner mouldings or reduced edge distances. This screw can be used in wood or steel up to a maximium thickness of 0.9 mm.



Features

Advantages

- 6-lohkoinen vetokärki
- Trim-pää
- Taltta
- Karkea kierre ja vastakierre
- Keltapinnoitettu sinkki

Applications

Support

- Puiset reunuslista
- Teräksinen reunus
- Kovapuiset lattiat puuhun

Technical Sheet

LTSFH
Skirting Screw Chisel Point

Technical Data



Mitat

Viite	Mitat							
	Tuotenumero	Muu	Mitat ja ominaisarvot[mm]					
		Paino[kg]	D[mm]	L[mm]	d_h[mm]	lg[mm]	l-lg[mm]	Bit[mm]
LTSFH4.2X42	74369	0.002	4.2	42	5.8	28	14	TX15
LTSFH4.2X57	74370	0.003	4.2	57	5.8	38	19	TX15

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00
Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta

Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita käytettäessä.