

Technical Sheet

LSF Skirting Screw

SIMPSON**Strong-Tie**

Used indoors for fixing skirting to underlying wood material. The small screw head has ribs on its underside for easy countersinking and a cutpoint to counteract splitting of the woodwork. The screw can also be fixed to a steel base with a maximum thickness of 0.6mm.

Features

Benefits

- Sylinterimäinen upotuspää: huomaamaton viimeistely
- Sen muotoilu mahdollistaa täydellisen viimeistelyn ja rajoittaa melua

Applications

Support

- Puiset jalkalistat
- Teräslista



Technical Sheet

LSF Skirting Screw

SIMPSON**Strong-Tie**

Technical Data

Product dimensions

Viite	Mitat							
	Tuotenumero	Muu	Mitat ja ominaisarvot[mm]					
		Paino[kg]	D[mm]	L[mm]	d _h [mm]	lg[mm]	l-lg[mm]	Bit[mm]
LSF3.0X35	75319	0.002	3	35	5.5	23	12	TX10
LSF3.0X42	75321	0.002	3	42	5.5	27	15	TX10
LSF3.0X57	75322	0.003	3	57	5.5	37	20	TX10

Maalattu pää RAL 9010

Viite	Mitat						
	Tuotenumero	Mitat ja ominaisarvot[mm]					
		D[mm]	L[mm]	d _h [mm]	lg[mm]	l-lg[mm]	Bit[mm]
LSF3.0X42 RAL9010	75323	3	42	5.5	27	15	TX10
LSF3.0X57 RAL9010	75324	3	57	5.5	37	20	TX10

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®

Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson Strong-Tie:n © tuotteita
käytettäessä.

LSF
Skirting Screw



www.strongtie.fi

2026-10-30

SIMPSON
Strong-Tie