

Technical Sheet

SIMPSON

Strong-Tie

LTSF Skirting Screw

The floor/skirting screw is used indoors for fixing skirting or when laying solid wood flooring, such as pine, oak and beech. The small screw head allows countersinking into the base material and the design helps prevent wooden floors creaking. Use with wood or steel maximum 0.6 mm.

Features

Features

- 6-lohkoinen vetokärki
- Leikkaa pannun pää
- Tyyppi 17 piste
- Karkea kierre käänteisellä kierteellä

Applications

Suitable for

- Jalkalista puuhun
- Teräslista
- Massiivipuulattia puuhun



LTSF
Skirting Screw

Technical Data

Mitat

Viite	Mitat							
	Tuotenumero	Muu	Mitat ja ominaisarvot[mm]					
		Paino[kg]	D[mm]	L[mm]	d _h [mm]	lg[mm]	l-lg[mm]	Bit[mm]
LTSF3.9X35	74371	0.002	3.9	35	5	23	12	TX10
LTSF3.9X42	74360	0.002	3.9	42	5	28	14	TX10
LTSF3.9X57	74381	0.002	3.9	57	5	38	19	TX10
LTSF3.9X70	74382	0.002	3.9	70	5	46	24	TX10

Maalattu pää RAL 9010

Viite	Mitat						
	Tuotenumero	Mitat ja ominaisarvot[mm]					
		D[mm]	L[mm]	d _h [mm]	lg[mm]	l-lg[mm]	Bit[mm]
LTSF3.9X42 RAL9010	74383	3.9	42	5	28	14	TX10
LTSF3.9X57 RAL9010	74384	3.9	57	5	38	19	TX10

