

Technical Sheet

SIMPSON

Strong-Tie

FSM

Steel to Steel Screw

Steel profile screws which is designed for joining reinforcement beams. The phosphated FSM is suited for fixing material up to 2x1.0 mm. The electrogalvanised FSM screw is suited for fixing material up to 2x2.0 mm.

Features


Features

- Ristipää.
- Litteä pää.
- Porakärki.
- Metallinen kierteitys.
- Fosfaattipinnoite vaihtoehto.
- Sähkögalvanoitu pinnoite vaihtoehto.

Applications

Suitable for

- Teräs teräkseen.



Technical Sheet

SIMPSON**Strong-Tie**

FSM

Steel to Steel Screw

Technical Data



Mitat

Viite	Mitat					
	Tuotenumero	Muu	Mitat ja ominaisarvot[mm]			
		Paino[kg]	D[mm]	L[mm]	d _h [mm]	Bit[mm]
FSM4.2X14	74398	0.001	4.2	14	7	PH2
FSM4.8X16	74397	0.002	4.8	16	8	PH2

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®

Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita
käytettäessä.

FSM
Steel to Steel Screw

2026-10-
24



www.strongtie.fi

SIMPSON**Strong-Tie**