

Technical Sheet

SIMPSON

Strong-Tie

CLN34G

Verhousnaula 34° paperiteippi - offset-pyöreä pää, rengasvarsi - HDG

The hot dip galvanised cladding nail is mainly used for painted facades. The length of the nail is developed to not penetrate the wind shield/protection behind the facade and the flat head covers the opened wood fibre after insertion.

The ring shank increase the withdrawal performance and the 60 degree diamond point prevents splitting.

Features


Advantages

- Offset-pyöreä pää
- 60 asteen timanttikärki
- Renkaankantainen varsi
- Kuumasinkitty
- Paperiteippi 34°

Applications

Support

- Verhous/julkisivupuu puuhun



Technical Sheet

SIMPSON**Strong-Tie**

CLN34G

**Verhousnaula 34° paperiteippi - offset-pyöreä pää,
rengasvarsi - HDG**

Technical Data

Product dimensions

Viite	Mitat				
	Tuotenumero	Muu	Mitat ja ominaisarvot[mm]		
CLN34G2.8X48	75		lg[mm]	lp[mm]	tfix[mm]
			28	2.4	24.

Product dimensions

See full table online [→](#)

Product characteristic properties

Viite	Nail characteristic parameters					
	Tyypillinen vääntölujuus - $f_{tor,k}$ [Nm]					
	Taivutuslujuus - $M_{y,k}$ [Nm]	Tyypillinen vetoparametri - $f_{ax,k,90^\circ}$ [N/mm ²]	Characteristic Head Pull-Through Parameter $f_{head,k}$ [N/mm ²]	Tyypillinen vetolujuus - $f_{tens,k}$ [kN]	Tyypillinen vääntölujuus - $f_{tor,k}$ [Nm]	Vääntösuhde
CLN34G2.8X48	2.5	7.1	12.8	-	-	-

Simpson Strong-Tie / Gbo
Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®

Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta

Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson Strong-Tie:n © tuotteita käytettäessä.

CLN34G

**Verhousnaula 34° paperiteippi - offset-pyöreä
pää, rengasvarsi - HDG**www.strongtie.fi**SIMPSON****Strong-Tie**

2026-10-30