

Technical Sheet

SIMPSON

Strong-Tie

HWPRO

Wallgrabb-levyn kiinnitys

Used indoors in plasterboard and fibreboard. The fixing is simply knocked into the base material with a hammer without any need for pre-drilling. Suitable screws are Ø3.5-4.5 mm wood or wafer head screws. As the board fixing is 30 mm long, use a screw measuring at least 30 mm plus the thickness of the plasterboard or fibreboard.



Features

Ominaisuuudet:

- Keltainen sinkitty
- Ei esiporausta
- Esiasennus
- Vetämisen estävä kaulus
- Nopea asennus
- Helppo irrottaa pienin vaurioin

Applications

Application:

- Kipsilevy



Technical Sheet

SIMPSON**Strong-Tie®**

HWPRO

Wallgrabb-levyn kiinnitys

Technical Data

Product dimensions



Viite	Plasterboard fixing dimensions[mm]	
	Tuotenumero	NOBB nr.
HWPRO3.0-4.5	75566	55837002

Simpson Strong-Tie / Gbo Fastening Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®

Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita
käytettäessä.

HWPRO
Wallgrabb-levyn kiinnitys

2026-10-
30



www.strongtie.fi

SIMPSON**Strong-Tie®**