

Technical Sheet

CLSZN

Wood Facade Screw Impreg®+

SIMPSON

Strong-Tie

Made for outdoor wood cladding. The flat head with fiber lock technology protects the wood from moisture, and the double thread ensures sufficient insertion, even in high density wood without the risk of spin-off. Impreg®+ version is made for painted facades

Features

Materiaali

- Korroosiosuoja: Impreg®+

Ominaisuudet:

- 6-lohkoinen vetokärki
- Litteä pää ja kuitulukitusmekanismi
- Kaksoiskierre
- Erittäin taipuisa

Applications

Sovellus

- Puijet julkisivut puuhun
- **VAROITUS:** Puuluokkaan T4 tai sitä korkeampaan luokkaan kuuluville sovelluksille ja erityisesti happamalle puulle (pH < 4, douglasmänty), suosittelemme CLS A4 -ruostumattomasta teräksestä valmistettua versiota.



CLSZN

Wood Facade Screw Impreg®+

Technical Data



Mitat

Viite	Mitat							
	Tuotenumero	Mitat ja ominaisarvot[mm]						
		D[mm]	L[mm]	dh[mm]	lg1[mm]	lg2[mm]	tfix[mm]	Bit[mm]
CLSZN4.8X48	75460	4.8	48	8	26	18	23	T-20
CLSZN4.8X48 Bulk	75459	4.8	48	8	26	18	23	T-20
CLSZN4.8X65	75462	4.8	65	8	26	22	40	T-20
CLSZN4.8X65 Bulk	75461	4.8	65	8	26	22	40	T-20

