

Technical Sheet

SIMPSON**Strong-Tie®****TTF**

Wood Fibre to Wood Screw

The TTF wood fibre board screw is used indoors for fastening OSB, chipboard and plywood to wood battens. The screws have cutpoint, which effectively drives the screws into hard wood.

Applications

Liitos


- Lastulevy puuhun.
- Vaneri puuhun.
- OSB puuksi.



TTF Wood Fibre to Wood Screw

Technical Data

Mitat ja ominaisarvot



Viite	Mitat					
	Tuotenumero	Mitat ja ominaisarvot[mm]				
		D[mm]	L[mm]	dh[mm]	lg[mm]	Bit[mm]
TTF4.2X35 PH2	75340	4.2	35	7	21	PH2
TTF4.2X45 PH2	75341	4.2	45	7	27	PH2
TTF4.2X45 PH Bulk	75342	4.2	45	7	27	PH2
TTF4.2X55 PH2	75343	4.2	54	7	30	PH2
TTF4.2X55 PH Bulk	75344	4.2	54	7	30	PH2
TTF4.2X55 PH Bulk XL	75338	4.2	54	7	30	PH2


TTF Sähkögalvanoitu, PH-kärki, sarjapakattu



Viite	Mitat						
	Tuotenumero	Mitat ja ominaisarvot[mm]					
		D[mm]	L[mm]	dh[mm]	hc[mm]	lg[mm]	Bit[mm]
TTF4.2X35 PH Collated	74279	4.2	35	7	10	21	PH2
TTF4.2X45 PH Collated	74280	4.2	45	7	20	27	PH2
TTF4.2X50 PH Collated	74281	4.2	50	7	25	30	PH2

* Flat tape collated for standard auto-feed screwdrivers

TTF Sähkögalvanoitu, 6-lehtinen



Viite	Mitat						
	Tuotenumero	Mitat ja ominaisarvot[mm]					
		D[mm]	L[mm]	dh[mm]	hc[mm]	lg[mm]	Bit[mm]
TTF4.2X35 T-20	74282	4.2	35	7	10	21	T20
TTF4.2X45 T-20	74283	4.2	45	7	20	27	T20
TTF4.2X55 T-20	74284	4.2	55	7	25	30	T20
TTF4.2X75 T-20	74285	4.2	75	7	35	42	T20

TTF Wood Fibre to Wood Screw

Tuotteen ominaisuudet

Viite	Screw Parameters			
	Tyypillinen vääntölujuus - $f_{tor,k}$ [Nm]			
	Taivutuslujuus - M_y,k [Nm]	Tyypillinen vetoparametri - $f_{ax,k,90^\circ}$ [N/mm ²]	Tyypillinen läpivetoparametri - $f_{head,k}$ [N/mm ²]	Tyypillinen vetolujuus - $f_{tens,k}$ [kN]
TTF4.2X35 PH2	4545	10.2	-	6.6
TTF4.2X45 PH2	4545	10.2	-	6.6
TTF4.2X45 PH Bulk	4545	10.2	-	6.6
TTF4.2X55 PH2	4545	10.2	-	6.6
TTF4.2X55 PH Bulk	4545	10.2	-	6.6
TTF4.2X55 PH Bulk XL	4545	10.2	-	6.6
TTF4.2X35 T-20	4545	10.2	-	6.6
TTF4.2X45 T-20	4545	10.2	-	6.6
TTF4.2X55 T-20	4545	10.2	-	6.6
TTF4.2X75 T-20	4545	10.2	-	6.6
TTF4.2X35 PH Collated	4545	10.2	-	6.6
TTF4.2X45 PH Collated	4545	10.2	-	6.6
TTF4.2X50 PH Collated	4545	10.2	-	-

