Technical Sheet

BW
Wood to Steel Drill Wing Screw

The drill wing screw, which is self-drilling and can be used outdoor, is used for fitting wood battens, wood fibreboards and fibercement boards to beams and steel joists. The wings remove material to a larger diameter than regular threads and prevent the threads engaging in the material, which means there is no need for pre-drilling before fitting.



Features

Features

- 6-lohkoinen vetokärki
- Uurrettu litteä pää
- Siipinen poranterä
- Metallinen kierteityskierre

Applications

Liitos

- Puu teräkseksi

Technical Sheet

BW
Wood to Steel Drill Wing Screw

Technical Data



Mitat ja ominaisarvot

Viite	Mitat								
	Tuotenumero	Muu	Mitat ja ominaisarvot[mm]						
		Paino[kg]	lg[mm]	D[mm]	L[mm]	d_h[mm]	Puun paksuus[mm]	Teräksen paksuus[mm]	Bit[mm]
BW4.2X45	74258	0.003	Filetage total	4.2	45	9.5	6 - 30	1 - 2	TX25
BW4.8X50	74259	0.004	Filetage total	4.8	50	9.5	10 - 38	2 - 4	TX25
BW4.8X85	74260	0.005	Filetage total	4.8	85	9.5	10 - 60	1 - 2	TX25
BW5.5X65	74262	0.006	Filetage total	5.5	65	12.1	10 - 40	2 - 4	TX30
BW5.5X85	74263	0.007	Filetage total	5.5	85	12.1	25 - 60	2 - 4	TX30
BW5.5X90	74270	0.008	Filetage total	5.5	90	12.1	25 - 55	4 - 12	TX30
BW5.5X115	74261	0.008	Filetage total	5.5	115	12.1	40 - 80	4 - 12	TX30

BW fosfatoitu, koottu*

Viite	Mitat					
	Tuotenumero	Mitat ja ominaisarvot[mm]				
		D[mm]	L[mm]	d_h[mm]	Teräksen paksuus[mm]	Bit[mm]
BW3.9X42	75723	3.9	42	11.5	2	PH2

* Flat tape collated for standard auto-feed screwdrivers

Copyright by Simpson Strong-Tie®
Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta
Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita käytettäessä.